

E.C. Material Safety Data Sheet

according to 93/112 EEC and 91/155 EEC
for the liquid

Tradename:

Demotec Easy Bloc

Demotec®

State: 1 dated 19.08.03
Print date: 19.08.03
Page: 1 / 8

1. Identification of the substance/preparation and of the company

Information on the product

Trade name:

Demotec Easy Bloc

Purpose: Liquid component of the 2-component-acrylic-system, serving to treat bovine lameness.

Information on the manufacturer

Demotec
Siegfried Demel
Brentanostraße 21
D-61130 Nidderau
Tel.: 0049 (0) 6187 - 21200

Emergency number in the case of poisoning

(in Germany, Berlin)
Giftnotrufzentrale-Berlin
Phone: 0049 (0) 30 - 19240

2. Composition/information on ingredients

Chemical characterization

Methacrylic acid methyl ester or methyl methacrylate

Hazardous ingredients

Methyl methacrylate

Concentration 60 to 100 %
CAS number 80-62-6
Hazard symbols Xi, F
R-phrases 11-36/37/38-43

3. Hazards identification

Highly flammable. Irritating to eyes, respiratory system and skin. May cause sensitization by skin contact.

4. First aid measures

General information

Remove soiled, soaked clothing immediately. Medical treatment is necessary if symptoms occur which are obviously caused by skin or eye contact with the product or by inhalation of its vapours.

After inhalation

Remove the casualty into fresh air and keep him calm. Supply with medical care.

After contact with skin

In case of contact with skin clean thoroughly with soap and water. A doctor must be consulted in case of skin irritation.

After contact with eyes

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

After swallowing

Summon a doctor immediately.

5. Fire-fighting measures

Suitable extinguishing media

Water spray jet, foam, dry powder, carbon dioxide.

E.C. Material Safety Data Sheet

according to 93/112 EEC and 91/155 EEC
for the liquid

Tradename:

Demotec Easy Bloc

Demotec®

State: 1 dated 19.08.03
Print date: 19.08.03
Page: 2 / 8

5. Fire-fighting measures - Continued

Unsuitable extinguishing media for safety reasons

Full water jet.

Special protective equipment for fire fighting

Use self-contained breathing apparatus. (Insulating apparatus).

6. Accidental related measures

Precautionary measures related to humans

Provide adequate ventilation. Use personal protective clothing.

Environmental protective measures

Prevent product from getting into drains/surface water/groundwater.

Methods of cleaning/absorption

Larger quantities:

Remove mechanically (by pumping). Observe EX-protection.

Smaller quantities and/or residues:

Absorb with absorbent material (e.g. sand, diatomaceous earth, acid absorbent, universal absorbent or sawdust).

7. Handling and storage

Handling

Instructions on safe handling

Keep containers tightly closed. Ensure the area is well ventilated.

Information on fire and explosion protection

Keep away from sources of ignition - no smoking. For larger quantities take precautionary measures against static charges. In the event of fire, cool the endangered containers with water.

Requirements for storage areas and containers:

Storage temperature: +10 to + 25 °C.

For short periods: - 20 to + 30 °C

Keep only in the original container at a temperature not exceeding 25 °C Fill the container to approximately 90 % only because oxygen (air) is required for stabilisation. Keep out of direct sunlight. For large storage quantities or storage of large packages exceeding 5 kg / 5 l an explosion-proof installation is required.

Other

Should the liquid cool down to under 10 °C, some particular dissolved ingredients may crystallize and stick to the ground of the container. When heated up to room temperature the crystals will mix up with the solvent. Please shake the tightly closed container well. There is no danger of reducing the processing qualities.

8. Exposure control and personal protection

Components or products of decomposition according to point 10, with limit values related to the place of work and requiring monitoring.

MAK-value for

CAS number 80-62-6

Methyl methacrylate 210 mg/m³ 50 ml/m³

Top demarcation category 1

Annotations/Notes/Observations

Sensitizing.

Y: No damage to harvests if MAK standards are complied with (TRGS 900).

E.C. Material Safety Data Sheet

according to 93/112 EEC and 91/155 EEC
for the liquid

Tradename:

Demotec Easy Bloc

Demotec®

State: 1 dated 19.08.03
Print date: 19.08.03
Page: 3 / 8

8. Exposure control and personal protection (Continued)

Personal protective equipment

General protective measures

Do not inhale vapours. Avoid contact with eyes and skin.

Hygiene measures

Store work clothing separately. Remove soiled or soaked clothing immediately.

Follow the usual trade-determined standards of hygiene.

Respiratory protection

Breathing apparatus in case of insufficient ventilation. Short term: filter appliance, filter A.

Hand protection

Gloves consisting of butyle – rubber. Time of protection 300 min (EN 374).

As deviating conditions may occur in the daily practice, these figures can only be an aid of orientation on the choice of an appropriate chemical protective glove. Especially they do not substitute suitability tests made by the consumer.

General protective measures

Protective gloves should be changed regularly, especially after intense contact with the product. For every work place an appropriate glove – type has to be chosen.

Eye protection

Wear tightly fitting safety goggles.

Body protection

When handling larger quantities: Face protection, chemical-proof boots and apron.

9. Physical and chemical properties

Appearance

Form: liquid
Colour: colourless
odour: ester - like

Data relevant to security (data for the component methyl methacrylate)

Changes in physical state

Melting temperature	- 48,2 °C	
Initial boiling point	approx. 100,3 °C	(at 1013 hPa)
Flash Point	10 °C	(Method DIN 51755)
Ignition temperature	430 °C	(Method DIN 51794)
Self ignition	Not determined	
Lower explosion limit	2,1 % vol	
Upper explosion limit	12,5 % vol	
Vapour pressure	38,7 hPa	(at 20 °C)
Density	0,94 g/cm ³	(at 20 °C)
Relative vapour density related to air	> 1	(at 20 °C)
Solubility in water	15,9 g/l	(at 20 °C)
Fat solubility	Not determined	
Solubility (qualitative)	mixeable with most organic solvents	
pH-value	not applicable	
n-octanol/Water distribution coefficient	log Pow 1,38	(measured, source literature)
viscosity dynamic	0,63 mPa.s	(at 20 °C, Method Brookfield)
Further information	None	

E.C. Material Safety Data Sheet

according to 93/112 EEC and 91/155 EEC
for the liquid

Tradename:

Demotec Easy Bloc

Demotec®

State: 1 dated 19.08.03
Print date: 19.08.03
Page: 4 / 8

10. Stability and reactivity

Thermal decomposition

No decomposition when used as directed.

Hazardous reactions

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides, reducing substances, and/or heavy metal ions).

Hazardous decomposition products

None when used as directed.

11. Toxicological information

The following data refer to the component methyl methacrylate

Toxicity

Findings: Damage to the mucous membranes in nose, throat and lungs. Degeneration of the olfactory epithelium. (Application method inhalative, application interval 6 h/d, 5d/w, application period 2 a, species mouse, source literature).

Acute oral toxicity: (LD 50, OECD 401) > 5000 mg/kg
(Species rat, source literature)

Acute inhalation toxicity: (LC 50) 29,8 mg/l
(Length of exposure 4h, species rat, source literature)

Acute dermal toxicity: (LD 50) > 5000 mg/kg
(Species rabbit, source literature)

Skin irritation not irritating
(Length of exposure 24 h, Species rabbit, Method Occlusive, FDA 1959 Draize. Source literature).

Irritant effect on the eyes not irritating
(species rabbit eye, method Draize, Source literature).

Sensitization

In sensitization tests on guinea pigs with and without adjuvant, both positive and negative results were found. On humans various types of allergic reactions have been observed with varying incidence (symptoms: headache, eye irritations, skin affections). Source Literature.

Carcinogenicity

Not carcinogenic in inhalation and feeding studies carried out on rats, mice and dogs.

Chronic toxicity **NOAEL** 25 ppm

Findings: Damage to the mucous membranes in nose, throat and lungs at 400 ppm. Degeneration of the olfactory epithelium. (Application method inhalative, application interval 6 h/d, 5d/w, application period 2 a, 25 – 400 ppm, , species rat, source literature).

Chronic toxicity **NOAEL** 2000 ppm

Findings: No toxicological effects.

(Application method in drinking water, application interval 7 d/w, application period 2 a, 6-2000 ppm, species rat, source literature).

Mutagenity

Both positive and negative results in mutagenity / genotoxicity tests. No experimental indication regarding genocity in vivo existing (Source literature).

Total results: **No mutating effect** according to international criteria. (Source literature).

Reproduction toxicity / Teratogenity

In tests on animals there were no indications regarding reproduction toxicity observed (Source literature).

Carcinogenicity

Non-carcinogenic in inhalation and feeding studies carried out on rats, mice and dogs. (Source literature).

Further information on toxicology

No further toxicological data. Avoid contact with skin and eyes as well as inhalation of product vapours.

E.C. Material Safety Data Sheet

according to 93/112 EEC and 91/155 EEC
for the liquid

Tradename:

Demotec Easy Bloc

Demotec®

State: 1 dated 19.08.03
Print date: 19.08.03
Page: 5 / 8

12. Ecological information

Information on elimination (persistence and degradability)

Biological decomposure easily biologically decomposeable, approx. 94 %
(Method OECD 301 C, duration of test 14 d, literature)

Ecotoxicological effect

Fish toxicity (LC50) > 79 mg/l
(Length of exposure 96 h, Species Oncorhynchus mykiss, rainbow trout, OECD 203, Source literature)

Daphnia toxicity (EC50) 69 mg/l
(Length of exposure 48 h, Species daphnia magna, OECD 202, Source Literature)
(NOEC Daphnia magna, OECD 202 part 2, period of flow 21d 37 mg/l, Source Literature)

Algae toxicity (EC3) 37 mg/l
(Species scenedesmus quadricauda, DIN 38412 part 9, 8 d, Source Literature)

Algae toxicity (EC50) 170 mg/l
(Length of exposure 96 h, Species selenastrum capricornutum, OECD 201, Source Literature)

Bacteria toxicity (EC0) 100 mg/l (Species pseudomonas putida)

Further information on ecology

Do not allow to enter soil, waterways or waste water.

13. Disposal considerations

Product (components, powder and liquid)

European waste code (EWC):

07 02 99 Not hardened plastic-/resin remnants, - moulding compounds and components.

Recommendation

Must be brought to an authorized special waste incineration plant in accordance with the regulations on special waste following local regulations.

Processing deposits (hardened plastics from both components)

Waste code/waste name: 17 02 03

Other hardened plastic waste.

Recommendation:

Can be deposited or incinerated in a special refuse incineration plant together with household refuse in consideration of the refuse disposing instructions according to the local official instructions.

Contaminated packaging

Can be incinerated in accordance with the local official instructions.

Recommendation

Cleaned packing materials can be deposited in the local recycling containers.

Recommended cleaning agent

Ethylacetate

14. Transport information

Overland transport

ADR/RID/GGVS/GGVE

Class: 3 Flammable liquid material

Kemler figure: 39

UN number: 1247

Packaging group: II

Danger label: 3

Proper shipping name: Methyl methacrylate, monomer, stabilized UN number 1247

E.C. Material Safety Data Sheet

according to 93/112 EEC and 91/155 EEC
for the liquid

Tradename:

Demotec Easy Bloc

Demotec®

State: 1 dated 19.08.03
Print date: 19.08.03
Page: 6 / 8

14. Transport information - Continued

Inland waterways transport

ADNR

Class 3
UN number: 1247
Packaging group: II
Danger label: 3

Proper shipping name: Methyl methacrylate, monomer, stabilized UN number 1247

Shipment by sea

IMDG/GGVSea

Class 3
EmS 3-07
Marine pollutant Packed (+/0):0
Packaging group: II

Proper shipping name: Methyl methacrylate, monomer, stabilized UN number 1247

Air transport

ICAO/IATA

Class 3
Packaging group: II

Proper shipping name: Methyl methacrylate, monomer, stabilized UN number 1247

DOT: UN 1247 Methyl methacrylate, monomer, stabilized

15. Regulatory information

Labelling in accordance with direction on hazardous materials (GefstoffV/EC)
requires labelling

Hazardous component(s) for labelling
contains Methyl methacrylate

Hazard symbols

Xi Irritant
F Highly flammable

Risk phrases (R-phrases)

11 Highly flammable.
36/37/38 Irritating to eyes, respiratory system and skin.
43 May cause sensitization by skin contact.

Security phrases (S-phrases)

9 Keep container in a well-ventilated place.
16 Keep away from sources of ignition — No smoking.
29 Do not empty into drains.
33 Take precautionary measures against static charges
24 Avoid contact with skin.
37 Wear adequate protective gloves
46 In case of swallowing seek immediately medical advice and show package or labelling.

National regulatory information

Classifying according to VbF Group A, Class I
Technical instruction air: Class II, para. 31.7- After coming into force of amendment 5.2.5
Peril to water classification: 1 (VwVwS, annexe 2)

Employment restrictions (see EU instruction 92/85/EEC)

- Observe protection of labour instructions regarding children and adolescents (Youth regulations law).

E.C. Material Safety Data Sheet

according to 93/112 EEC and 91/155 EEC
for the liquid

Tradename:

Demotec Easy Bloc

Demotec®

State: 1 dated 19.08.03
Print date: 19.08.03
Page: 7 / 8

- Observe protection of labour instructions regarding expecting and nursing mothers (Maternity regulations law).

E.C. Material Safety Data Sheet

according to 93/112 EEC and 91/155 EEC
for the liquid

Tradename:

Demotec Easy Bloc

Demotec®

State: 1 dated 19.08.03
Print date: 19.08.03
Page: 8 / 8

16. Other information

Indications on sources

Relevant manuals and publications, toxicological and ecotoxicological studies of other producers. (SIAR, OECD-SIDS, RTK public files).

The product is normally supplied in a stabilized form. If the permissible storage period and/or storage temperature is noticeably exceeded, the product may polymerize with heat evolution.

The details are based on the present knowledge we have achieved; they are intended as a description of the products safety requirements and not to be seen as a guarantee of certain product features.

EC-Safety-Data sheet according to 91/155 EEC

for the powder

Demotec®

Trade name:

Demotec Easy BlocState: 0/28.08.03
Pages: 1 of 4**1. Identification of substance, preparation and company****Information on the product**

Trade name: DemotecEasy Bloc

Purpose: Powder component of the 2-component acrylic system serving to treat bovine lameness.

Manufacturer / supplierCompany
Demotec
Siegfried Demel
Brentanostraße 21
D-61130 Nidderau
Phone.: 0049 (6187) 21200**Emergency no. in the case of poisoning**
Giftnotrufzentrale Berlin
Phone No. 0049 (30) 19240**2. Composition / information on contents****Chemical characterization**

Preparation, Acryl polymere on basis of methyl methacrylate with barbiture acid as activator.

Dangerous components**Barbiture acid derivate**Concentration < 1 %
CAS-No. 837-32-1
Risk symbols Xi
Risk phrases
(R Phrases) 36/38**3. Hazards identification**

May cause irritations to the skin and eyes. May cause sensitization by skin contact.

4. First-Aid measures

After inhalation: In case of dyspnoea remove the casualty into fresh air. Summon a doctor, if symptoms occur.

After swallowing: In case of symptoms summon a doctor immediately.

After contact with skin: In case of contact with the skin wash off immediately with water and soap. In case of skin irritations consult the doctor.

After contact with eyes: In case of contact with eyes rinse thoroughly with open eyelid and with plenty of water and consult the doctor.

5. Measures for fire fighting

Suitable extinguishing media: Water spraying jet, foam, dry powder, carbon dioxide.

Unsuitable extinguishing media for safety reasons: Full water jet.

Special protective equipment for fire fighting: Self-contained breathing apparatus (Insulating apparatus).

Indications for the fire brigade / fire fighter:At the beginning fires can be extinguished with water. As soon as the burning resin develops into a fusion burning at a small flame it will react on water like burning fat or oil. In tests a fire – extinguishing gel (so-called connected hydro-gel, e.g. of the company *Hydrex*) has proven as the most efficient extinguishing medium.

EC-Safety – Data sheet according to 91/155 EEC
for powder of

Demotec®

Trade name:

Demotec Easy Bloc

Status: 0/28.08.03
Page: 2 of 4

6. Accidental release measures

Precautionary measures related to humans

Avoid dust formation. Use a respiratory protection in case of effect of vapours, dust, aerosol. Wear personal protective clothing.

Methods of cleaning / absorption

Take up mechanically and dispose of according to regulations.

7. Handling and storage

Handling

Instructions on safe handling

Avoid dust formation and dust deposits. No eating, drinking, smoking, food at working place.

Information on fire- and explosion protection

At higher quantities take measures against electrostatic charges.

In the event of fire, the endangered product should be cooled with water.

Storage

Requirements for storage areas and containers

Storage: dry; keep away from direct sunlight / avoid intense heating up.

8. Exposure controls / personal protection

Components or products of decomposition according to point 10, with limit values related to the place of work which require monitoring

MAK (GFG) value for

Methyl methacrylate 210 mg/m³

CAS-Number 80-62-6

Top demarcation Category 1

Annotations/Notes/Observations

Sensitizing

Y: No damage to harvests if MAK standards are complied with (TRGS 900).

Personal protective equipment

General protective measures:

Do not inhale dust.

Hygiene measures:

Follow the usual trade-determined standards of hygiene.

Respiratory protection:

Wear filtering half mask during dust formation. Fine powder mask P2 is necessary when the MAK value is exceeded.

Eye protection:

Tightly fitting protective goggles.

Hand protection:

Protective gloves according to EN 388.

Notice:

As the product is used with the appropriate liquid (solvent), we recommend as hand protective material butyl-rubber.

9. Physical and chemical properties

Appearance

Form: powder / hard

Odour: faint inherent odour

Colour: grey

Changes in physical state

Softening point:

Acryl polymere

approx. 100 °C

Calium carbonate

not applicable

Boiling temperature:

not applicable

not applicable

EC-Safety – Data sheet according to 91/155 EEC
for powder of

Demotec®

Trade name:

Demotec Easy Bloc

Status: 0/28.08.03
Page: 3 of 4

9. Physical and chemical properties - Continued

<u>Changes in physical state</u>	<u>Acryl polymere</u>	<u>Calium carbonate</u>
Flash point:	> 250 °C	not applicable
Ignition temperature:	> 400 °C	not applicable
Self ignition:	not determined	no data
Lower explosion limit:	not determined	not applicable
Upper explosion limit:	not determined	not applicable
Vapour pressure:	not applicable	not determined
Density:	1,18 g/cm ³	2,6-2,8 g/m ³ (at 20 °C)
Bulk density:	approx. 720 kg/m ³	not applicable
Water solubility:	insoluble	0,014 g/l (at 20 °C)
Solubility/qualitative:	Esters, ketones and chlorinated hydrocarbons: readily soluble	not applicable
pH value:	not applicable	8,5-9,5 (100g/l / at 20 °C)
Viscosity dynamic:	not applicable	not applicable

Further information

The possibility of dust explosions is generally to be expected with dust-forming organic products.

10. Stability and reactivity

Thermal decomposition

Acryle polymere > 250 °C

Calium carbonate > 825 °C

Hazardous reactions

No hazardous reactions are known.

Substances to be avoided:

Avoid contact with other chemicals.

Avoid contact with strong alkali and acids.

Hazardous decomposition products

None if employed as directed.

At thermal decomposition flammable, irritating vapours, irritating to eyes and respiratory system, especially consisting of: **Methyl methacrylate** will form.

11. Toxicological information

Further information on toxicology

There are no toxicological data available on this product. The fine particles contained in the product may cause mechanical irritations to the skin, eyes and mucous membranes. Avoid contact with skin and eyes. Avoid inhalation of product dust.

12. Ecological information

Further information on ecology


Do not allow to enter soil, waterways or waste water.

13. Disposal considerations

Product (components, powder and liquid)

European waste code (EWC): **07 02 99**

Not hardened plastic-/resin remnants, - moulding compounds and components.

EC-Safety – Data sheet according to 91/155 EEC for powder of Trade name: <div style="text-align: center;">Demotec Easy Bloc</div>	
	Status: 0/28.08.03 Page: 4 of 4

13. Disposal considerations - Continued

Recommendation
 Must be brought to an authorized special waste incineration plant in accordance with the regulations on special waste following local regulations.

Processing deposits (hardened plastics from both components)

Waste code/waste name: 17 02 03 Other hardened plastic waste.

Recommendation:
 After polymerisation it can be deposited or incinerated in a special refuse incineration plant together with household refuse in consideration of the refuse disposing instructions according to the official local instructions.

Contaminated packaging

Can be incinerated in accordance with the official local instructions.

Recommendation

Cleaned packing materials can be deposited in the local recycling containers.

Recommended cleaning agent

Ethylacetate

14. Transport information

Transport/further indications: No hazardous good within the sense of the transport regulations.

15. Regulatory information

Labelling in accordance with GefStoff/EC: labelling not required

Special regulations for preparations according to instruction 1999/45/EU Annexe V Part B
 "Contains methyl methacrylate, dibenzoyl peroxide. May cause allergic reactions".

National regulatory information

Peril to water classification: 1 (Self-assessment)

Employment restrictions (see EU instruction 92/85/EEC)

- Observe protection of labour instructions regarding children and adolescents (Youth regulations law).
- Observe protection of labour instructions regarding expecting and nursing mothers (Maternity regulations law).

16. Other information

None!

The details are based on the present knowledge we have achieved; they are intended as a description of the products safety requirements and not to be seen as a guarantee of certain product features.